

MATRIZ DE EVALUACIÓN

FILTROS GAS DE SELLO						EMPRESA		
ITEM	COD SAP	DESCRIPCIÓN SAP	DESCRIPCIÓN ALTERNATIVA	CANTIDAD	UN.	CANT.	UN.	CUMPLIMIENTO
1	11021202	ELEMENTO FILTRANTE JPMG 2510-R	ELEMENTO FILTRANTE MARCA: JONELL MODELO: JPMG 2510-R ESPECIFICACIONES: OD 2.5" / 112mm ID 1" / 76mm LENGTH 10" / 914 mm Media: Microglass Core: Tinned Steel End Caps: Tinned Steel Drain Layer: Needled Polyester Gaskets: Buna Micron Rating: 0.3µ at 99.98% efficiency Recommended Initial DP: < 0.5 psid Recommended Change-Out DP: 15 psid Maximum Operating Temperature: 275°F Burst Pressure > 75 psid Flow Direction: Inside to Out Configuration: Double Open End	60	pza	60	pza	CUMPLE/NO CUMPLE
TIEMPO DE ENTREGA: 10 DIAS CALENDARIO						CUMPLE/NO CUMPLE		
LUGAR DE ENTREGA: DDP ALMACEN DE SANTA CRUZ						CUMPLE/NO CUMPLE		
RESULTADO						HABILITADA/NO HABILITADA		